



JUMP TO A SERIES

	RECON 360 [®] TL BIPODS [NEW]	122
1	UTG PRO® TBNR® BIPODS	125
1	BIG BORE FULL STABILITY BIPOD	127
	OVER BORE BIPOD	129
I	RECON FLEX® BIPODS	131
	D GRIP®	132
ı	QUICK DETACH BIPODS	133

(I HIRD PARTY TRADEMARKS MAY BE USED IN THIS CATALOG FOR USER CONVENIENCE
TO INDICATE THE FIT OR COMPATIBILITY OF THE APPLICABLE PRODUCT.)





RECON 360° TL

As the name implies, the RECON 360® TL series of bipods feature a smooth 360° panning capability with the addition of 15° forward, rearward, left, and right tilt. Panning and tilting tension is adjustable by the end-user to fine-tune the desired amount of resistance and feedback required to pan and tilt the bipod. Tension adjustment is made quick and easy with a centrally located throw lever at the base of the bipod's mount. The throw lever is not only user friendly, but user serviceable and can be readjusted over time as the bipod wears in.

Suitable for different long gun applications, Recon 360 TL bipods are available in three different lockable and adjustable center-heights and are available in both M-LOK® and MIL-STD-1913 Picatinny mount configurations. Additionally, MIL-STD-1913 Picatinny mount models come included with a swivel stud mount adaptor, further increasing its compatible versatility right out-of-the-box.

FINE-TUNE ADJUSTMENT

Tension Adjustment Throw Lever is User Friendly and Serviceable being re-adjustable



3 POSITION FOLDING 0°, 45°, and 90° Foldable Positions

VERSATILE PANNING & TILTING

Smooth 360° panning with additional 15° forward, rearward, left, and right tilt.









RECON 360® TL BIPODS







5.8" - 7.1" Center Height / TL-BPM02-B 6.6" - 9.1" Center Height / TL-BPM01-B 8.1" - 11.9" Center Height / TL-BPM03-B

US PAT. D758522



6.6" - 9.1" Center Height / TL-BP01-B 8.1" - 11.9" Center Height / TL-BP03-B

US PAT. D758521, US PAT. D758522

RECON 360® TL BIPODS NEW

- » Durable Aircraft Aluminum Construction Finished in a Matte Black Anodization
- » 3 Position Folding Legs and Lockable Leg Extensions Equipped with Nonslip Rubberized Foot Pads
- » Tunable Tension Adjustment Applies the Desired Amount of Tension to the Bipod's 360° Panning & 15° Left, Right, Forward, and Rearward Tilt
- » Readjustable Tension Adjustment Lever is User Serviceable and Optimizes the Applied Tension with the Lever's Throw Distance and Positioning
- » Swivel Stud Adaptor Included (Picatinny Version Only)

	TL-BPM02-B	TL-BPM01-B	TL-BPM03-B	TL-BP02-B	TL-BP01-B	TL-BP03-B
Mount Type	M-LOK®	M-LOK®	M-LOK®	Picatinny	Picatinny	Picatinny
Center Height	5.8" - 7.1"	6.6" - 9.1"	8.1" - 11.9"	5.6" - 7.2"	6.6" - 9.1"	8.1" - 11.9"
Open Angle	50°	50°	50°	50°	50°	50°
Panning	360°	360°	360°	360°	360°	360°
Tilting (Forward, Rearward, Left, & Right)	15°	15°	15°	15°	15°	15°
Foot Pad	Rubberized	Rubberized	Rubberized	Rubberized	Rubberized	Rubberized
Weight	8.9 oz	11.3 oz	15.3 oz	10.9 oz	12.2 oz	14.5 oz
Extendable Legs	3 Position	5 Position	7 Position	3 Position	5 Position	7 Position
Leg Operation		Man	ual, 3 Position I	oldable & Lock	kable	



WWW.LEAPERS.COM **SINCE 1992**

TBNR® | THE BEST NEVER REST | BIPODS



M-LOK®

8.5" - 11.0" Center Height / TLUBP01M 7.3" - 9.0" Center Height / TLUBPO2M-A

PICATINNY

8.5" - 11.0" Center Height / TLUBP01 7.3" - 9.1" Center Height / TLUBPO2-A

UTG PRO®

TBNR® | THE BEST NEVER REST | BIPODS



Performance Tested and Evaluated



Height Adjustable Spiral Guided 7075-T6 Aluminum Leg Extensions Tilt Forward, Rearwith Automatic Leg **Extension Retraction** (US PAT. 10323897)



Tension Adjustable 360° Panning & 19° ward, Left, and Right



0°, 45°, & 90° Folding Leg Positions with Steel-on-steel Lockup

	TLUBP01M	TLUBP01M TLUBP02M-A		TLUBP02-A	
Mount Type	M-LOK®	M-LOK®	Picatinny	Picatinny	
Center Height	8.5" - 11.0"	7.3" - 9.0"	8.5" - 11.0"	7.3" - 9.1"	
Open Angle	50°	50°	50°	50°	
Panning	360°	360°	360°	360°	
Tilting	19°	19°	19°	19°	
Foot Pad	Aluminum	Aluminum	Aluminum	Aluminum	
Weight	19.0 oz	17.2 oz	19.7 oz	18.3 oz	
Extendable Legs	7 Position	4 Position	7 Position	4 Position	
Leg Operation		Manual, 3 Position F	oldable & Lockable		



BIG BORE FULL STABILITY BIPOD





BIG BORE FULL STABILITY BIPOD

- » Matte Black Anodized Aluminum Construction with Reinforced Steel Components Designed from the Ground Up to Withstand Big Bore Calibers up to .50 BMG
- » Reinforced Picatinny Mounting Base Features a Longer Surface Area Equipped with a Squared Steel Crossbolt
- » Lockable and Height Adjustable Legs Provide a Center Height from 9"-14" and a Wide 70° Open Angle for Increased Stability
- » Posi-lock Push Buttons Feature a Large Surface Area for Easier Use while Wearing Gloves

9.4" - 14.0" Center Height / TL-BPFS01-A



0°, 45°, & 90° Folding Leg Positions with Steel-on-steel Lockup



Tension Adjustable 35° Panning and 55° Left and Right Tilt



Rotatable Footpads Self Adjust to Uneven Surfaces and Bipod Leg Positioning

	TL-BPFS01-A
Mount Type	Picatinny
Center Height	9.4" - 14.0"
Open Angle	70°
Panning	35°
Tilting (Left/Right)	55°
Foot Pad	Steel
Weight	34.4 oz
Extendable Legs	9 Position
Leg Operation	Manual, 3 Position Foldable & Lockable



WWW.LEAPERS.COM | SINCE 1992

OVER BORE BIPOD



OVER BORE BIPOD

- » Wide Open Angle Improves Stability
- » Matte Black Anodized Aircraft Aluminum Construction with Reinforced Steel Components
- » 3 Position Folding Legs Equipped with Rubberized Foot Pads
- » Lockable and Height Adjustable Legs Providing a Center Height from 7"-11"
- » 22° Panning and 44° Tension Adjustable Left and Right Tilt
- » Posi-lock Push Buttons Feature a Large Surface Area for Easier Use while Wearing Gloves

7.3" - 11.4" Center Height / TL-BPOB01-A



Quick Detachable Mounting Base (Designed to Mount Under or Over Rifle Bore)



0°, 45°, & 90° Folding Leg Positions with Steel-on-steel Lockup



Oversized Posi-lock Push Buttons for Easier Use while Wearing Gloves



Tension Adjustable 44° Left & Right Tilt

	TL-BPOB01-A
Mount Type	Picatinny
Center Height	7.3" - 11.4"
Open Angle	70°
Panning	22°
Tilting (Left/Right)	44°
Foot Pad	Rubberized
Weight	24.1 oz
Extendable Legs	7 Position
Leg Operation	Manual, 3 Position Foldable & Lockable



RECON FLEX® BIPODS









RECON FLEX®

M-LOK® / 5.7" - 8.0" Center Height / TL-BPDM01 M-LOK® / 8.0" - 11.8" Center Height / TL-BPDM02 KEYMOD / 5.7" - 8.0" Center Height / TL-BPDK01

RECON FLEX® II BIPODS

- » 5 Position Bidirectional Legs Feature One-piece Locking Sliders with Circular Locking Lugs for Easier Manipulation and Added Durability
- » Interchangeable Foot Pads Compatible with Most Aftermarket Pads with QD Locking Detent
- » Automatic Leg Extension Deployment
- » Height Extendable Legs Lockable Via Thumb Wheel

RECON FLEX® BIPODS

- » Ergonomic Spring Loaded Slide Locking Ring for Quick and Effortless Bipod Deployment
- » Legs with 5 Posi-lock Positions for Use on Different Firearms with Varying Height Clearance and Mounting Real Estate
- » Height Extendable Legs Lockable Via Thumb Wheel
- » US PAT 10295292



Directly Attaches to Handguard at the 3 and Folding Legs 9 O'clock Positions



5 Position Bidirectional

	TL-BPDM03	TL-BPDM04	TL-BPDM01	TL-BPDM02	TL-BPDK01
Mount Type	M-LOK®	M-LOK®	M-LOK®	M-LOK®	Keymod
Center Height	7.1" - 9.1"	8.7" - 12.0"	5.7" - 8.0"	8.0" - 11.8"	5.7" - 8.0"
Open Angle	50°	50°	50°	50°	50°
Foot Pad	Rubberized	Rubberized	Rubberized	Rubberized	Rubberized
Weight (2pcs)	11.3 oz	12.3 oz	10.8 oz	13.7 oz	10.8 oz
Extendable Legs	5 Position	7 Position	5 Position	7 Position	5 Position
Leg Operation	Manual, 5 Position Foldable & Lockable				



D GRIP®







D GRIP®

- » Contoured Foregrip with Nonslip and Heat-resistant Rubberized Inlays
- » Ambidextrous Quick Release Deploys Foldable Impact-resistant Bipod Legs Instantly
- » Quickly Transitions from Foregrip to Bipod
 » 5.6" Foregrip Length with an 8.4" Center Height and
- 65° Open Angle when Bipod is Deployed

 >> US PAT. 8397421, US PAT. 9169958, EU REG:

 002245522-0001, EU REG: 002245522-0002

/ MNT-DG02Q

	MNT-DG02Q
Mount Type	Picatinny
Center Height	8.4"
Open Angle	65°
Grip Height	5.6"
Bipod Height	8.6"
Foot Pad	Aluminum
Weight	12.7 oz
Leg Operation	Spring Loaded Deployment

WWW.LEAPERS.COM | SINCE 1992

QUICK DETACH BIPODS





- » Protected Rubber Armored Legs Stands up to the Harshest of Environments
- » 5 Position Extendable Legs Lockable via Thumb Wheel
- » 5 Position Bidirectional Folding Legs
- » US PAT. 8397421

QD Lever Lock / 6.0" - 8.5" Center Height / TL-BP20Q-A



TACTICAL OP BIPODS

- » Heavy Duty Steel and Aluminum Construction with a Matte Black Finish
- » Spring-loaded Folding Legs
- » Fully Adjustable Legs with Locking Thumb Wheel & Automatic Retraction
- » US PAT. 8397421

QD Lever Lock / 5.9" - 7.3" Center Height / TL-BP78Q
QD Lever Lock / 8.0" - 12.4" Center Height / TL-BP88Q
Locking Thumb Wheel / 6.1" - 7.9" Center Height / TL-BP78
Locking Thumb Wheel / 8.3" - 12.7" Center Height / TL-BP88



SUPER DUTY QD BIPODS

- » Heavy Duty Steel and Aluminum Construction with a Matte Black Finish
- » Spring-loaded Folding Legs
- » Fully Adjustable Legs with Spring Loaded Retention Clamp and Locking Thumb Wheel
- » US PAT. 8397421

QD Lever Lock / 6.0" - 8.5" Center Height / TL-BP98Q QD Lever Lock / 8.0" - 12.8" Center Height / TL-BP99Q

	TL-BP20Q-A	TL-BP78Q	TL-BP88Q	TL-BP78	TL-BP88	TL-BP98Q	TL-BP99Q	
Mount Type		Picatinny						
Center Height	6.0" - 8.5"	5.9" - 7.3"	8.0" - 12.4"	6.1" - 7.9"	8.3" - 12.7"	6.0" - 8.5"	8.0" - 12.8"	
Open Angle	50°	50°	50°	50°	50°	50°	50°	
Panning	15°	15°	15°	15°	15°	15°	15°	
Foot Pad	Rubberized	Rubberized	Rubberized	Rubberized	Rubberized	Rubberized	Rubberized	
Weight	14.0 oz	13.0 oz	12.8 oz	11.5 oz	13.3 oz	13.8 oz	17.4 oz	
Extendable Legs	5 Position	3 Position	7 Position	3 Position	7 Position	5 Position	9 Position	
Foldable Legs	5 Position	Yes	Yes	Yes	Yes	Yes	Yes	
Swivel Stud Kit	Included	Included	Included	Included	Included	Included	Included	
Leg Operation	Manual, 5 Position Foldable & Lockable	Spring Loaded						

SWIVEL STUD TO PICATINNY ADAPTOR

- » Steel and Aluminum Construction with Padded Adaptor Plate to Prevent Marring
- » Converts a Traditional Sling Swivel Stud to Accept Picatinny Mounted Bipods
- » Retains Swivel Stud Functionality for the Installation of a Sling when Installed
- » Quick to Install with No Permanent Modification Required
 - / TL-BPAD1