

BIPODS

A man wearing a black cap, large headphones, and a tan t-shirt is aiming a tan-colored rifle. The rifle is mounted on a bipod and has a large scope. He is positioned behind a large, weathered log in a forest setting with green trees and foliage in the background.

ROCK SOLID FOUNDATION

Purpose-built across a multitude of disciplines with one common goal: a rock solid shooting interface. Try our new GOLIATH™ bipods for precision long distance, our slim 2-piece RECON FLEX® line for stowing while hunting, or a classic spring-loaded solution. Whether you need pan and tilt or a specific angle, height, or deployment method, our wide selection is designed to solve your every need.



JUMP TO A SERIES

GOLIATH™ BIPODS [NEW]	122
BIG BORE FULL STABILITY BIPOD	124
OVER BORE BIPOD	126
UTG PRO®  TBNR® BIPODS	128
RECON 360® TL BIPODS	130
RECON FLEX® BIPODS	132
QUICK DETACH BIPODS	134
D GRIP®	135

[THIRD PARTY TRADEMARKS MAY BE USED IN THIS CATALOG FOR USER CONVENIENCE TO INDICATE THE FIT OR COMPATIBILITY OF THE APPLICABLE PRODUCT.]



GOLIATH™



GOLIATH™ BIPODS



MEDIUM PROFILE

8.01" - 12.24" Center Height
/ TL-BPFS02Q



EXTREME LOW PROFILE

5.90" - 8.05" Center Height
/ TL-BPFS03Q



GOLIATH™ BIPODS

NEW

- » Big Bore Construction for Long Distance Precision Shooting Up to .50 BMG, Available in Medium and Extreme Low Profile (5.9" - 8")
- » Wide 60° Open Angle for Improved Stability
- » Independent Tension Adjustable 40° Tilting and 28° Panning Left and Right
- » Three-position Foldable and Center Height Adjustable Legs Lock with Authority at Each Position and Height
- » Tool-free Tension Adjustable QD Picatinny Base with Squared Integral Recoil Lugs
- » Matte Black Anodized Aluminum and Steel Construction



Independent Tension Adjustable 40° Tilting and 28° Panning Left and Right



Center Height Adjustable Legs Lock with Authority at Each Position and Height



QD Rubber Oversized Feet for Added Traction, Compatible with Most Aftermarket QD Foot Pads

	TL-BPFS02Q	TL-BPFS03Q
Mount Type	Picatinny	Picatinny
Center Height	8.01" - 12.24"	5.90" - 8.05"
Open Angle	60°	60°
Tension Adjustable Panning	28°	28°
Tension Adjustable Tilting	40°	40°
Extendable Leg Positions	14	7
Extension Method	Manual	Manual
Retraction Method	Manual	Manual
Foldable Positions	0°, 45°, 90°	0°, 45°, 90°
Foot Pad	XL Rubberize Pad	XL Rubberize Pad
Weight	27.0 oz (773 g)	24.5 oz (695 g)

BIG CORE FS



BIG BORE FULL STABILITY BIPOD



BIG BORE FULL STABILITY BIPOD

- » Matte Black Anodized Aluminum Construction with Reinforced Steel Components Designed from the Ground Up to Withstand Big Bore Calibers up to .50 BMG
- » Reinforced Picatinny Mounting Base Features a Longer Surface Area Equipped with a Squared Steel Crossbolt
- » Lockable and Height Adjustable Legs Provide a Center Height from 9.61"-14.30" and a Wide 70° Open Angle for Increased Stability
- » Posi-lock Push Buttons Feature a Large Surface Area for Ease of Use while Wearing Gloves



0°, 45°, & 90° Folding Leg Positions with Steel-on-steel Lockup



Tension Adjustable 35° Panning and 55° Left and Right Tilt



Rotatable Footpads Self Adjust to Uneven Surfaces and Bipod Leg Positioning

	TL-BPFS01-A
Mount Type	Picatinny
Center Height	9.61" - 14.30"
Open Angle	70°
Tension Adjustable Panning	35°
Tension Adjustable Tilting	55°
Extendable Leg Positions	9
Extension Method	Manual
Retraction Method	Automatic
Foldable Positions	0°, 45°, 90°
Foot Pad	Steel
Weight	34.9 oz (991 g)

OVERGORE



OVER BORE BIPOD



OVER BORE BIPOD

- » Wide Open Angle and Lowered Center of Gravity Improves Stability
- » Quick Detachable Picatinny Base Designed to Mount at the 12 O'clock
- » 3 Position Foldable with Lockable Notched Legs, Center Height Adjustable from 7.20" - 10.96"
- » 22° Panning and 44° Tension Adjustable Left and Right Tilt
- » Matte Black Anodized Aluminum Construction with Reinforced Steel Components



Quick Detachable Mounting Base Designed to Mount Over Rifle Bore



0°, 45°, & 90° Folding Leg Positions with Steel-on-steel Lockup



Tension Adjustable 44° Left & Right Tilt

	TL-BPOB01-A
Mount Type	Picatinny
Center Height	7.20" - 10.96"
Open Angle	70°
Tension Adjustable Panning	22°
Tension Adjustable Tilting	44°
Extendable Leg Positions	7
Extension Method	Manual
Retraction Method	Manual
Foldable Positions	0°, 45°, 90°
Foot Pad	Rubberized
Weight	24.1 oz (683 g)

ADDITIONAL ACCESSORIES

OVER BORE BIPOD QD MOUNT

- » Quick Detachable Picatinny Mount for the UTG® Over Bore Bipod (One Piece Included with TL-BPOB01-A)
- » Allows a Single Over Bore Bipod to be Quickly Removed and Attached Between Multiple Rifles
- » Tension Adjustment Knob Controls the Amount of Tension Felt when Tilting

/ TL-BPAD2



THE BEST NEVER REST®



TBNR® BIPODS



M-LOK®

8.59" - 11.02" Center Height / TLUBP01M
7.24" - 9.05" Center Height / TLUBP02M-A

PICATINNY

8.57" - 11.09" Center Height / TLUBP01
7.22" - 9.03" Center Height / TLUBP02-A



UTG PRO® TBNR® BIPODS

- » 3 Position Folding with Steel-on-steel Lockup
- » Patented Height Adjustable Spiral Guided Leg Extensions with Steel Ball Bearing Detent Ring Locks Manages Height Adjustment and Retention
- » Interchangeable Foot Pads Compatible with Most Aftermarket Pads with QD Locking Detent
- » Type III Class 2 Matte Black Hard Coat Anodized 6061-T6 and 7075-T6 Aluminum Construction with Reinforced Steel Components
- » US PAT. 10323897, US PAT. 10690434



Performance Tested and Evaluated



Height Adjustable Spiral Guided 7075-T6 Aluminum Leg Extensions with Automatic Leg Retraction



Tension Adjustable 360° Panning & 19° Tilt Forward, Rearward, Left, and Right



0°, 45°, & 90° Folding Leg Positions with Steel-on-steel Lockup

	TLUBP01M	TLUBP02M-A	TLUBP01	TLUBP02-A
Mount Type	M-LOK®	M-LOK®	Picatinny	Picatinny
Center Height	8.59" - 11.02"	7.24" - 9.05"	8.57" - 11.09"	7.22" - 9.03"
Open Angle	50°	50°	50°	50°
Tension Adjustable Panning	360°	360°	360°	360°
Tension Adjustable Tilting	19°	19°	19°	19°
Extendable Leg Positions	8	6	8	6
Extension Method	Manual	Manual	Manual	Manual
Retraction Method	Automatic	Automatic	Automatic	Automatic
Foldable Positions	0°, 45°, 90°	0°, 45°, 90°	0°, 45°, 90°	0°, 45°, 90°
Interchangeable Foot Pad	Aluminum	Aluminum	Aluminum	Aluminum
Swivel Stud Kit Included	No	No	Yes	Yes
Weight	19.0 oz (539 g)	17.5 oz (496 g)	19.7 oz (558 g)	18.3 oz (519 g)

RECON 360® TL



RECON 360® TL BIPODS



M-LOK®

5.70" - 7.00" Center Height / TL-BPM02-B
6.69" - 9.10" Center Height / TL-BPM01-B
8.10" - 11.99" Center Height / TL-BPM03-B

US PAT. D758522

PICATINNY

5.68" - 7.10" Center Height / TL-BP02-B
6.64" - 9.10" Center Height / TL-BP01-B
7.82" - 12.00" Center Height / TL-BP03-B

US PAT. D758521, US PAT. D758522



RECON 360® TL BIPODS

- » RECON 360® Smooth 360° Panning with Additional 15° Tilt Forward, Rearward, Left, and Right
- » Panning and Tilting Tension Adjustable with Throw Lever at Mount Base
- » Tension Adjustment Throw Lever is Use Serviceable to Readjust Over Time
- » 3 Lockable and Adjustable Center Heights with Included Swivel Stud Mount Adaptor for Picatinny Models



FINE-TUNE ADJUSTMENT
Tension Adjustment Throw Lever is User Friendly and Serviceable being re-adjustable over time



VERSATILE PANNING & TILTING
Smooth 360° panning with additional 15° forward, rearward, left, and right tilt

	TL-BPM02-B	TL-BPM01-B	TL-BPM03-B	TL-BP02-B	TL-BP01-B	TL-BP03-B
Mount Type	M-LOK®	M-LOK®	M-LOK®	Picatinny	Picatinny	Picatinny
Center Height	5.70" - 7.00"	6.69" - 9.10"	8.10" - 11.99"	5.68" - 7.10"	6.64" - 9.10"	7.82" - 12.00"
Open Angle	50°	50°	50°	50°	50°	50°
Tension Adjustable Panning	360°	360°	360°	360°	360°	360°
Tension Adjustable Tilting	15°	15°	15°	15°	15°	15°
Extendable Leg Positions	3	5	7	3	5	7
Extension Method	Manual	Manual	Manual	Manual	Manual	Manual
Retraction Method	Manual	Manual	Manual	Manual	Manual	Manual
Foldable Positions	0°, 45°, 90°	0°, 45°, 90°	0°, 45°, 90°	0°, 45°, 90°	0°, 45°, 90°	0°, 45°, 90°
Foot Pad	Rubberized	Rubberized	Rubberized	Rubberized	Rubberized	Rubberized
Swivel Stud Kit Included	No	No	No	Yes	Yes	Yes
Weight	11.1 oz (316 g)	11.3 oz (320 g)	14.6 oz (416 g)	12.2 oz (347 g)	13.6oz (386g)	15.7 oz (447 g)

RECON FLEX[®]



RECON FLEX® BIPODS



RECON FLEX® BIPODS

- » Low Profile Separated Legs Attach to M-LOK® Handguards at 3 and 9 O'clock Positions
- » Lightweight, Wide Angle Stance, and Slum Low Profile when Stowed
- » 5 Position Bidirectional Folding with Recon Flex® II Featuring Automatic Leg Extension Deployment



RECON FLEX® II BIPODS

- » 5 Position Foldable with Lockable Notched Legs and Automatic Leg Extension Deployment
- M-LOK®**
7.30" - 8.87" Center Height / TL-BPDM03
8.37" - 12.08" Center Height / TL-BPDM04



RECON FLEX® BIPODS

- » 5 Position Foldable with Lockable Notched Legs
- M-LOK®**
5.96" - 8.39" Center Height / TL-BPDM01
8.13" - 11.95" Center Height / TL-BPDM02
- KEYMOD**
5.96" - 8.39" Center Height / TL-BPDK01

	TL-BPDM03	TL-BPDM04	TL-BPDM02	TL-BPDM01	TL-BPDK01
Mount Type	M-LOK®	M-LOK®	M-LOK®	M-LOK®	Keymod
Center Height	7.30" - 8.87"	8.37" - 12.08"	8.13" - 11.95"	5.96" - 8.39"	5.96" - 8.39"
Open Angle	50°	50°	50°	50°	50°
Extendable Leg Positions	5	8	7	5	5
Extension Method	Automatic	Automatic	Manual	Manual	Manual
Retraction Method	Manual	Manual	Manual	Manual	Manual
Foldable Positions	0°, 45°, 90°, 135°, 180°	0°, 45°, 90°, 135°, 180°	0°, 45°, 90°, 135°, 180°	0°, 45°, 90°, 135°, 180°	0°, 45°, 90°, 135°, 180°
Foot Pad	Rubberized, Interchangeable	Rubberized, Interchangeable	Rubberized	Rubberized	Rubberized
Weight (2pcs)	11.3 oz (320 g)	12.2 oz (346 g)	14 oz (398 g)	10.8 oz (306 g)	10.8 oz (306 g)



QUICK DETACH BIPODS



SUPER DUTY QD BIPOD

- » Heavy Duty Steel and Aluminum Construction with a Matte Black Finish
- » Spring-loaded Folding Legs
- » Adjustable Legs with Spring Loaded Retention Clamp and Locking Thumb Wheel
- » US PAT. 8397421

QD Lever Lock / 5.56" - 8.00" Center Height / TL-BP98Q

ADDITIONAL ACCESSORIES

SWIVEL STUD TO PICATINNY ADAPTOR

- » Steel and Aluminum Construction with Rubber Contact Plate to Prevent Marring
- » Converts a Traditional Sling Swivel Stud to Accept Picatinny Mounted Bipods
- » Retains Sling Swivel Stud Functionality when Installed
- » Quick Installation with No Permanent Modification Required

/ TL-BPAD1





RUBBER ARMORED QD BIPOD

- » Protected Rubber Armored Legs Stand up to the Harshesht of Environments
- » 5 Position Extendable Legs Lockable via Thumb Wheel
- » 5 Position Bidirectional Folding Legs
- » US PAT. 8397421

QD Lever Lock / 6.05" - 8.52" Center Height / TL-BP20Q-A



TACTICAL OP BIPODS

- » Heavy Duty Steel and Aluminum Construction with a Matte Black Finish
- » Spring-loaded Folding Legs
- » Adjustable Legs with Locking Thumb Wheel & Automatic Retraction
- » US PAT. 8397421

QD Lever Lock / 6.24" - 7.37" Center Height / TL-BP78Q
QD Lever Lock / 8.22" - 12.59" Center Height / TL-BP88Q
Locking Thumb Wheel / 5.80" - 7.50" Center Height / TL-BP78
Locking Thumb Wheel / 8.00" - 12.40" Center Height / TL-BP88

	TL-BP98Q	TL-BP20Q-A	TL-BP78Q	TL-BP88Q	TL-BP78	TL-BP88
Mount Type	Picatinny	Picatinny	Picatinny	Picatinny	Picatinny	Picatinny
Center Height	5.56" - 8.00"	6.05" - 8.52"	6.24" - 7.37"	8.22" - 12.59"	5.80" - 7.50"	8.00" - 12.40"
Open Angle	50°	50°	50°	50°	50°	50°
Panning	15°	15°	15°	15°	15°	15°
Extendable Leg Positions	5	5	3	9	Continuous	Continuous
Extension Method	Manual	Manual	Manual	Manual	Manual	Manual
Retraction Method	Manual	Manual	Automatic	Automatic	Automatic	Automatic
Foldable Positions	0°, 90°	0°, 45°, 90°, 135°, 180°	0°, 90°	0°, 90°	0°, 90°	0°, 90°
Foot Pad	Rubberized	Rubberized	Rubberized	Rubberized	Rubberized	Rubberized
Swivel Stud Kit Included	Yes	Yes	Yes	Yes	Yes	Yes
Weight	13.8 oz (391 g)	12.4 oz (374 g)	11.9 oz (338 g)	15.5 oz (440g)	11.9 oz (338 g)	15.5 oz (440g)

D GRIP®



- » Ambidextrous Quick Release Deploys Foldable Impact-resistant Bipod Legs Instantly
- » Quickly Transitions from Foregrip to Bipod
- » Contoured Foregrip with Rubberized Inlays
- » 5.60" Foregrip Length with an 8.20" Center Height and 65° Open Angle when Bipod is Deployed
- » US PAT. 8397421, US PAT. 9169958, EU REG: 002245522-0001, EU REG: 002245522-0002

	MNT-DG02Q
Mount Type	Picatinny
Center Height	8.20"
Open Angle	65°
Grip Height	5.60"
Bipod Height	8.20"
Leg Operation	Spring-loaded Deployment
Foot Pad	Aluminum
Weight	12.7 oz (360 g)