



## **UTG PRO® P.O.I® SCOPE MOUNTS**

Proudly made in USA, UTG Pro P.O.I rings boast a patented steel locking interface controlled by dual spring-loaded guide rods for easy and solid installation. Top and bottom rings are precision-cut from a single piece of 6061-T6 Aluminum using Palletec-automated Mazak HCN4000 horizontal milling machines. By machining the top ring, bottom ring, and Picatinny interface in one operation centricity is guaranteed for your optic and your rail. No compromise on the most important tolerances and priced affordably out of Livonia, Michigan.

## **UTG® ACCU-SYNC® CANTILEVER MOUNTS**

UTG Accu-Sync Cantilever mounts are a staple for any tactical build and available across 1 inch, 30 mm and 34 mm sizes at a multitude of heights and offsets. The base torx screw-locking model features lightening cuts for weight savings and is a historical best seller. The Quick Release option includes tool-free adjustment, lockable levers, and saloon-style locking direction to minimize snag. MOA compensation also available across 20, 30, and 40 MOA angles.

# UTG PRO® P.O.I® SCOPE MOUNTS

TORX SCREW LOCKING MOUNT | PATENTED P.O.I LOCKING PLATE WITH DUAL SPRING-LOADED GUIDE RODS

**.50 BMG Rated**



## CANTILEVER MOUNT **NEW** 7075-T6 Aluminum

Patented locking plate with dual spring-loaded guide rods for repeatable zero.

1.35" center height and 3.7" offset tailored for Service Rifle competition.

Square Picatinny recoil stops for secure zero hold.

US PAT. D771218 | EU PAT. EP2761064-0001

**34 MM Ø** | Picatinny

Center Height 1.35" (34 mm)

Offset 3.7" (94 mm)

**SERVICE RIFLE** / RI34135C (ADDITIONAL SKUS COMING SOON)

## 2-PIECE RINGS

EU PAT. EP2691725-0001 | EU PAT. EP2761064-0001 | US PAT. D771218



**1" Ø** | Picatinny

Center Height 0.91" (23 mm)

/ RWU012510

Center Height 1.1" (28 mm)

/ RWU012515

Center Height 1.3" (33 mm)

/ RWU012520

**30 MM Ø** | Picatinny

Center Height 0.98" (25 mm)

/ RWU013010

Center Height 1.18" (30 mm)

/ RWU013015

Center Height 1.46" (37 mm)

/ RWU013022

**34 MM Ø** | Picatinny

Center Height 1" (25 mm)

/ RWU013408

Center Height 1.26" (32 mm)

/ RWU013415

Center Height 1.46" (37 mm)

/ RWU013420

**1" Ø** | Dovetail

Center Height 1.1" (28 mm)

/ RDU012515

Center Height 1.3" (33 mm)

/ RDU012520

**30 MM Ø** | Dovetail

Center Height 0.98" (25 mm)

/ RDU013010

Center Height 1.18" (30 mm)

/ RDU013015

Center Height 1.46" (37 mm)

/ RDU013022

# UTG® ACCU-SYNC® CANTILEVER MOUNTS

TORX SCREW LOCKING MOUNT | 6061-T6 ALUMINUM | PICATINNY

**.338 LAPUA MAGNUM Rated**

**1" Ø**

Center Height 1.22" (31 mm) | Offset 1.34" (34 mm)  
/ AIR11834

Center Height 1.22" (31 mm) | Offset 1.97" (50 mm)  
/ AIR11850

Center Height 1.38" (35 mm) | Offset 1.34" (34 mm)  
/ AIR12234

Center Height 1.38" (35 mm) | Offset 1.97" (50 mm)  
/ AIR12250

**30 MM Ø**

Center Height 1.3" (33 mm) | Offset 1.34" (34 mm)  
/ AIR31834

Center Height 1.3" (33 mm) | Offset 1.97" (50 mm)  
/ AIR31850

Center Height 1.46" (37 mm) | Offset 1.34" (34 mm)  
/ AIR32234

Center Height 1.46" (37 mm) | Offset 1.97" (50 mm)  
/ AIR32250

**34 MM Ø**

Center Height 1.54" (39 mm) | Offset 1.97" (50 mm)  
/ AIR42250



# UTG® ACCU-SYNC® QR CANTILEVER MOUNTS

LOCKING QUICK RELEASE LEVER MOUNT | TOOL-FREE TENSION ADJUSTMENT | PICATINNY **.338 LAPUA MAGNUM** Rated



## UTG® ACCU-SYNC® ANTI-CANT LEVELERS

Magnetic flip-to-side anti-cant bubble leveler easily seen through peripherals without having to break target focus and or adjust cheek weld.

Compatible with UTG Accu-Sync cantilever mounts only.

US PAT. 11293721

- 1" Ø** / MT-RTF1
- 30 MM Ø** / MT-RTF3
- 34 MM Ø** / MT-RTF4

Includes cover plate and Docter® and RMR® footprint compatible optic plates.



- 1" Ø** / MT-RTR1
- 30 MM Ø** / MT-RTR3
- 34 MM Ø** / MT-RTR4



### 1" Ø

Center Height 1.22" (31 mm) | Offset 1.34" (34 mm)  
/AIR11834Q

Center Height 1.22" (31 mm) | Offset 1.97" (50 mm)  
/AIR11850Q

Center Height 1.38" (35 mm) | Offset 1.97" (50 mm)  
/AIR12250Q

### 30 MM Ø

Center Height 1.46" (37 mm) | Offset 1.34" (34 mm)  
/AIR32234Q

Center Height 1.46" (37 mm) | Offset 1.97" (50 mm)  
/AIR32250Q

### 34 MM Ø

Center Height 1.54" (39 mm) | Offset 2.76" (70 mm)  
/AIR42270Q

## MOA COMPENSATION

### 70 MM OFFSET

#### 20 MOA | 0.33° Tilted Degree

- 34 MM Ø** /AIR420MOA
- 30 MM Ø** /AIR320MOA

#### 30 MOA | 0.50° Tilted Degree

- 34 MM Ø** /AIR430MOA
- 30 MM Ø** /AIR330MOA

#### 40 MOA | 0.67° Tilted Degree

- 34 MM Ø** /AIR440MOA
- 30 MM Ø** /AIR340MOA



## 2-PIECE RINGS

### 1" Ø

Center Height 0.89" (22.7 mm)  
/AQR110

Center Height 1.09" (27.7 mm)  
/AQR115

Center Height 1.29" (32.7 mm)  
/AQR120

### 30 MM Ø

Center Height 0.98" (25 mm)  
/AQR310

Center Height 1.18" (30 mm)  
/AQR315

Center Height 1.46" (37 mm)  
/AQR322

### 34 MM Ø

Center Height 1.26" (32 mm)  
/AQR415

Center Height 1.46" (37 mm)  
/AQR420

Center Height 1.54" (39 mm)  
/AQR422

Center Height 1.93" (49 mm)  
/AQR432

# UTG® SCOPE MOUNTS

## 2-PIECE PICATINNY RINGS | Twist Lock

### 1" Ø

Center Height 0.91" (23 mm)  
/RG2W1104

Center Height 1.1" (28 mm)  
/RG2W1154

Center Height 1.3" (33 mm)  
/RG2W1204

### 30 MM Ø

Center Height 0.98" (25 mm)  
/RG2W3104

Center Height 1.18" (30 mm)  
/RG2W3154

Center Height 1.46" (37 mm)  
/RG2W3224



## 2-PIECE PICATINNY RINGS | Hex Thumb Nut

### 1" Ø

Center Height 0.91" (23 mm)  
/RGWM-25L2

Center Height 1.06" (27 mm)  
/RGWM-25M4

Center Height 1.22" (31 mm)  
/RGWM-25H4

### 30 MM Ø

Center Height 0.94" (24 mm)  
/RGWM-30L4

Center Height 1.14" (29 mm)  
/RGWM-30M4

Center Height 1.46" (37 mm)  
/RGWM-30H4



## 2-PIECE DOVETAIL RINGS | Hex

### 1" Ø

Center Height 1.06" (27 mm)  
/RGPM-25M4

Center Height 1.34" (34 mm)  
/RGPM-25H4

### 30 MM Ø

Center Height 1.14" (29 mm)  
/RGPM-30M4

Center Height 1.42" (36 mm)  
/RGPM-30H4



## DOVETAIL INTEGRAL MOUNT | Hex

### 1" Ø

Center Height 1.06" (27 mm)  
/RGPM2PA-25M4

Center Height 1.34" (34 mm)  
/RGPM2PA-25H4



### 1" Ø | Offset Mount

Center Height 1.34" (34 mm)  
Offset 1.50" (38 mm)  
/RGPM0FS38-25H4



# RECEIVER MOUNTS



## UTG PRO® FOR RUGER® 10/22®

Length 4.67" (119 mm)  
Picatinny Slots 11  
6061-T6 Aluminum  
/MTU030T22

## UTG PRO® FOR MOSSBERG® 500®/590®

Length 5.5" (139.7 mm)  
Picatinny Slots 13  
6061-T6 Aluminum  
/MTU029SG

## UTG PRO® FOR REMINGTON® 870™/1100™

Length 6.1" (155 mm)  
Picatinny Slots 14  
6061-T6 Aluminum  
/MTU028SG

## UTG® FOR REMINGTON® 700®

Picatinny Slots 6  
Steel

**LONG ACTION** /MNT-RM700

**SHORT ACTION** /MNT-RM700S

## UTG® FOR SPRINGFIELD ARMORY® M14/M1A

Length 6.10" (155 mm)  
Picatinny Slots 15  
Aluminum

/MNT-914V2

# UTG® SHOTGUN SIDE SADDLE MOUNTS

## FOR MOSSBERG® 500® / 590® / 590M®

Removable 4-Capacity shot shell carrier included.  
6061-T6 Aluminum

**FOR MOSSBERG® 500®/590®** /MT-MB590

**FOR MOSSBERG® 590M®** /MT-MB590M



## FOR REMINGTON® 870™

Removable 4-Capacity shot shell carrier included.

Compatible with 12 Gauge Remington® 870™ and 870 DM shotguns with up to a 3.5" chambering.

6061-T6 Aluminum

/MT-RM870



# UTG® SUPER SLIM PICATINNY RISER MOUNTS

U.S. PATENT: [www.leapers.com/patents](http://www.leapers.com/patents)

## 3-SLOT

Length 1.6" (40.6 mm)  
6061-T6 Aluminum

**0.50" SADDLE HEIGHT** /MT-RSX5S

**0.75" SADDLE HEIGHT** /MT-RSX7S

**0.83" SADDLE HEIGHT** /MT-RSX8S

**1.00" SADDLE HEIGHT** /MT-RSX1S



## 13-SLOT

Length 5.5" (139.7 mm)  
6061-T6 Aluminum

**0.50" SADDLE HEIGHT** /MT-RSX5L

**0.75" SADDLE HEIGHT** /MT-RSX7L

**0.83" SADDLE HEIGHT** /MT-RSX8L

**1.00" SADDLE HEIGHT** /MT-RSX1L

**20 MOA COMPENSATED** /MT-RSX20MOA





## UTG® DOVETAIL TO PICATINNY MOUNTS



### FOR ROUND/FLAT DOVETAIL RECEIVER

Compatible with 9–11mm flat or rounded Dovetail rails.

US PAT. 10352656 | EU PAT. EP3196588

Length 5.71" (145 mm)  
Picatinny Slots 14  
Saddle Height 0.59" (15 mm)  
Cantilevered Offset 2" (51.8 mm)  
6061-T6 Aluminum

/MNT-DTW145



### FOR FLAT DOVETAIL RECEIVER

Compatible with 9–11mm flat Dovetail rails.

US PAT. D837330

Length 3.94" (100 mm)  
Picatinny Slots 9  
Saddle Height 0.56" (14.32 mm)  
6061-T6 Aluminum

/MNT-PMTOWL-A



### SNAP-ON RAIL ADAPTOR

Spring-loaded adjustable Dovetail width from 9–11mm.

US PAT. 8752325

Length 1" (25.4 mm)  
Picatinny Slots 1 Each  
Aluminum and Steel

**SET OF 2** /MNT-DT2PW01

## UTG® DEDICATED PICATINNY OPTIC MOUNTS



### 45° OFFSET

**FOR DOCTER® FOOTPRINT** /RDM-2045

**FOR RMR® FOOTPRINT** /MT-RMR45



### LOW PROFILE

**FOR RMR® FOOTPRINT** /MT-RMRXS

### LOW PROFILE & ABSOLUTE CO-WITNESS

**FOR RMR® FOOTPRINT** /MT-RMRKIT



### ABSOLUTE CO-WITNESS

**FOR DOCTER® FOOTPRINT** /RDM-20AC

**FOR RMR® FOOTPRINT** /MT-RMRAC



### LOWER 1/3 CO-WITNESS

**FOR RMR® FOOTPRINT** /MT-RMR13C



**FOR AIMPOINT® MICRO FOOTPRINT** /MT-T1AC



**FOR AIMPOINT® MICRO FOOTPRINT** /MT-T113C

## UTG® DEDICATED DOVETAIL OPTIC MOUNTS

### FOR GLOCK® REAR SIGHT DOVETAIL

**FOR DOCTER® FOOTPRINT** /RDM-20GL

**FOR RMR® FOOTPRINT** /MT-RMRGL



### FOR 9–11MM FLAT/ROUND DOVETAIL | LOW PROFILE

**FOR DOCTER® FOOTPRINT** /RDM-20XSD

